



ANSI E1.39 – 2015  
Entertainment Technology – Selection and Use of Personal  
Fall Arrest Systems on Portable Structures Used in the  
Entertainment Industry

Document number Rig/2009-2017r6

**This standard was approved as an American National Standard by ANSI's Board of Standards Review on 28 January 2015.**

**© 2015 by PLASA North America**

**[This page intentionally left blank]**

## NOTICE and DISCLAIMER

PLASA does not approve, inspect, or certify any installations, procedures, equipment or materials for compliance with codes, recommended practices or standards. Compliance with a PLASA standard or an American National Standard developed by PLASA is the sole and exclusive responsibility of the manufacturer or provider and is entirely within their control and discretion. Any markings, identification or other claims of compliance do not constitute certification or approval of any type or nature whatsoever by PLASA.

PLASA neither guarantees nor warrants the accuracy or completeness of any information published herein and disclaims liability for any personal injury, property or other damage or injury of any nature whatsoever, whether special, indirect, consequential or compensatory, directly or indirectly resulting from the publication, use of, or reliance on this document.

In issuing and distributing this document, PLASA does not either (a) undertake to render professional or other services for or on behalf of any person or entity, or (b) undertake any duty to any person or entity with respect to this document or its contents. Anyone using this document should rely on his or her own independent judgment or, as appropriate, seek the advice of a competent professional in determining the exercise of reasonable care in any given circumstance.

### Published by:

PLASA North America  
630 Ninth Avenue, Suite 609  
New York, NY 10036  
USA  
Phone: 1-212-244-1505  
Fax: 1-212-244-1502  
[standards.na@plasa.org](mailto:standards.na@plasa.org)

## The PLASA Technical Standards Program

The PLASA Technical Standards Program was created to serve the PLASA membership and the entertainment industry in technical standards related matters. The goal of the Program is to take a leading role regarding technology within the entertainment industry by creating recommended practices and standards, monitoring standards issues around the world on behalf of our members, and improving communications and safety within the industry. PLASA works closely with the technical standards efforts of other organizations within our industry as well as representing the interests of PLASA members to ANSI, UL, and the NFPA. The Technical Standards Program is accredited by the American National Standards Institute.

The Technical Standards Council (TSC) was established to oversee and coordinate the Technical Standards Program. Made up of individuals experienced in standards-making work from throughout our industry, the Council approves all projects undertaken and assigns them to the appropriate working group. The Technical Standards Council employs a Technical Standards Manager to coordinate the work of the Council and its working groups as well as maintain a “Standards Watch” on behalf of members. Working groups include: Control Protocols, Electrical Power, Floors, Fog and Smoke, Followspot Position, Photometrics, Rigging, and Stage Lifts.

PLASA encourages active participation in the Technical Standards Program. There are several ways to become involved. If you would like to become a member of an existing working group, as have over four hundred people, you must complete an application which is available from the PLASA office. Your application is subject to approval by the working group and you will be required to actively participate in the work of the group. This includes responding to letter ballots and attending meetings. Membership in PLASA is not a requirement. You can also become involved by requesting that the TSC develop a standard or a recommended practice in an area of concern to you.

The Rigging Working Group, which authored this Standard, consists of a cross section of entertainment industry professionals representing a diversity of interests. PLASA is committed to developing consensus-based standards and recommended practices in an open setting.

The Technical Standard Program (TSP) is financially supported by PLASA and by companies and individuals who make undirected donations to the TSP. Contributing companies and individuals who have helped fund the TSP are recognized as “Investors in Innovation.” The Investors in Innovation for the twelve months prior to this standard being published on 28 January 2015 include these companies and individuals:

**VISIONARY (\$10,000 AND UP)**

LDI  
ProSight Specialty Insurance  
United States Institute for Theatre Technology

**INNOVATOR (\$3,000 - \$9,999)**

Barbizon Electric  
ETC  
Mountain Productions Inc.

**DEVELOPER (\$1,000 - \$2,999)**

Candela Controls Inc  
Jahn Hardison  
Stage Equipment & Lighting, Inc.  
Ultratec Special Effects Inc.  
View One, Inc.

**TRENDSETTER (\$500 - \$999)**

Clark-Reder Engineering  
Doug Fleenor Design, Inc.  
Ed Hyatt  
ELS / Entertainment Lighting Services  
Entertainment Structures Group  
IATSE International  
John T. McGraw  
MDG Fog Generators Ltd  
Oasis Stage Werks  
Ralph Weber  
Steve Walker  
Vincent Lighting Systems

**GROUNDBREAKER (\$200 - \$499)**

Boston Illumination Group, Inc.  
Eddie Kramer  
H & H Specialties Inc.  
Hot Springs Convention Center & Summit  
Arena  
IATSE Local 514  
Indianapolis Stage Sales & Rentals, Inc.  
Ken Production Services, Inc.  
Lightstream, Inc  
Louis Bradfield  
McLaren Engineering Group  
TEI Electronics, Inc.  
Total Structures, Inc.

**SUPPORTER (\$100 - \$199)**

AC Power Distribution, Inc.  
Kent Jorgensen  
Michael LaNinfa  
Musique Xpress Lights, Inc.  
Strohmeier Lighting, Inc.  
Tony Giovannetti

All donations to the TSP support the Technical Standards Program in general and are not directed to or for the benefit of any particular technical standard project or any Working Group working on any particular standard or project.

---

**Contact Information****Technical Standards Manager**

Karl G. Ruling  
PLASA North America  
630 Ninth Avenue, Suite 609  
New York, NY 10036  
USA  
1-212-244-1505  
[karl.ruling@plasa.org](mailto:karl.ruling@plasa.org)

**Assistant Technical Standards Manager**

Erin Grabe  
PLASA North America  
630 Ninth Avenue, Suite 609  
New York, NY 10036  
USA  
1-212-244-1505  
[erin.grabe@plasa.org](mailto:erin.grabe@plasa.org)

**Technical Standards Council Chairpersons**

Mike Garl  
Mike Garl Consulting LLC  
836 Smoke Creek Rd.  
Knoxville, TN 37934  
USA  
1-865-389-4371  
[mike@mikegarlconsulting.com](mailto:mike@mikegarlconsulting.com)

Mike Wood  
Mike Wood Consulting LLC  
6401 Clairmont Drive  
Austin, TX 78749  
USA  
1-512-288-4916  
[mike@mikewoodconsulting.com](mailto:mike@mikewoodconsulting.com)

**Rigging Working Group Chairperson**

Bill Sapsis  
Sapsis Rigging, Inc.  
233 North Lansdowne Ave.  
Lansdowne, PA 19050  
USA  
1-215-228-0888 x206  
[bill@sapsis-rigging.com](mailto:bill@sapsis-rigging.com)

## Acknowledgments

The Rigging Working Group members when this document was approved by the working group on 19 November 2014 were as follows:

### Voting members:

Mike Adamovich; M.G. McLaren, P.C.; G  
Jesse Adams; Rose Brand; DR  
Mark Ager; Tait Towers Manufacturing LLC; CP  
Matthew Antonucci; Contract Services Administration Trust Fund; U  
Dana Bartholomew; Tait Towers Manufacturing LLC; CP  
William Beautyman; Limelight Productions, Inc.; DR  
Nils Becker; Electronic Theatre Controls, Inc.; MP  
Patrick Leigh Bettington; Tait Towers Manufacturing LLC; CP  
Ian Bevan; Walt Disney Company; U  
Scott M. Blair; Full Throttle Films/ VER; DR  
Steve (BOZ) Bodzioch; LMG Inc.; DR  
Keith Bohn; G  
Vincent J. Cannavale; Motion Laboratories; CP  
David Carmack; Columbus McKinnon Corp.; MP  
Joseph Champelli; Entertainment Project Services, LLC; DE  
Stu Cox; ZFX Flying Inc.; CP  
Dan Culhane; SECOA; CP  
Bruce Darden; Rigging Innovators, Inc.; CP  
Robert Dean; ZFX Flying Inc.; CP  
Jonathan Deull; JSD Projects LLC; U  
Brad Dittmer; Stage Labor of the Ozarks; U  
Russ Dusek; I Weiss; MP  
Douglas M. Eldredge; LMG Inc.; DR  
Patrick Finn; Wenger Corp.; CP  
Nick Fleming; Walt Disney Company; U  
Adrian Forbes-Black; Total Structures Inc.; MP  
Howard Forryan; Harting KGAA; G  
Mike Garl; Mike Garl Consulting LLC; DE  
Ed Garstkiewicz; Harting KGAA; G  
Ethan William Gilson; Advanced Lighting and Production Services; U  
William B. Gorlin; M.G. McLaren, P.C.; G  
Jerry Gorrell; Theatre Safety Programs; G  
Earle T. Greene; Walt Disney Company; U  
Pat Grenfell; Hoist Sales & Service; DR  
Joshua Grossman; Schuler Shook; DE  
Joel A Guerra; Texas Scenic Company; DR  
Don Halchak; Total Structures Inc.; MP  
Rod Haney; I.A.T.S.E. Local 891; U  
Tim Hansen; Oasis Stage Werks; DR  
Pete Happe; Walt Disney Company; U  
Sandy Harned; ZFX Flying Inc.; CP  
Herb Hart; Columbus McKinnon Corp.; MP

David Herrmann; Motion Laboratories; CP  
Peter Herrmann; Motion Laboratories; CP  
Jeremy Hochman; Full Throttle Films/ VER; DR  
Donald A. Hoffend\_Jr.; Avista Designs, LLC; G  
Donald Hoffend\_III; Avista Designs, LLC; G  
Christopher Jacobs; Virginia Beach City Public Schools; U  
Joseph Jeremy; Show Distribution Group; MP  
Scott Johnson; Milos Group; MP  
Ted Jones; Chicago Spotlight, Inc.; U  
Christine L. Kaiser; Syracuse Scenery & Stage Lighting Co., Inc.; DR  
Theresa Kelley; Total Structures Inc.; MP  
Jerald Kraft; JTH Lighting Alliance; CP  
Edwin S. Kramer; I.A.T.S.E. Local 1; U  
Kyle Kusmer; Steven Schaefer Associates; G  
Roger Lattin; I.A.T.S.E. Local 728; U  
Jon Lenard; Applied Electronics; MP  
Michael Lichter; Electronic Theatre Controls, Inc.; MP  
Dan Lisowski; University of Wisconsin - Madison; U  
Marcus Lopez Jr.; LMG Inc.; DR  
Joseph McGeough; Foy Invention Enterprises, Inc.; CP  
Bob McVay; Schuler Shook; DE  
Sam Michael; Thern, Inc.; MP  
Steven Michelman; Entertainment Project Services, LLC; DE  
Orestes Mihaly; Production Resource Group; DR  
Jeff T. Miller; Walt Disney Company; U  
Rick Montgomery; R&M Materials Handling; MP  
John P. Moore; Hall Associates Flying Effects; CP  
Reid Neslage; H & H Specialties Inc.; MP  
Mark Newlin; Xtreme Structures and Fabrication; MP  
Richard J. Nix; Steven Schaefer Associates; G  
Jyle Noguee; Texas Scenic Company; DR  
Shawn Nolan; Production Resource Group; DR  
Tracy Nunnally; Hall Associates Flying Effects; CP  
Kimberly Corbett Oates; Schuler Shook; DE  
Jennifer O'Leary; Columbus McKinnon Corp.; MP  
Carlos Ortega; PSAV Presentation Services; U  
Gregory Orth; WNP Services, Inc.; DR  
Edward A. (Ted) Paget; Electronic Theatre Controls, Inc.; MP  
Michael Parrella; Arup; DE  
Miriam Paschetto; Geiger Engineers; G  
Rocky Paulson; Freeman Companies; DR  
Galen Price; Blue Man Group; U  
Woody Pyeatt; A V Pro, Inc.; DR  
Gregory Quinkert; Motion Laboratories; CP  
Robert Ramsey; WNP Services, Inc.; DR  
Steven Ricks; Electronic Theatre Controls, Inc.; MP  
John Ringelman; Freeman Companies; DR



Jean-Philippe Robitaille; Show Distribution Group, Inc.; MP  
 Rick Rosas; Texas Scenic Company; DR  
 Shawn Sack; A.C.T. Lighting; DR  
 Bill Sapsis; Sapsis Rigging, Inc.; U  
 Peter A. Scheu; Scheu Consulting Services, Inc.; DE  
 Chris Schmidt; Freeman Companies; DR  
 Joseph S. Schuster; Simpson Gumpertz & Heger; DE  
 Steven C. Shaw; Levitating Productions, Inc.; MP  
 John C. Snook; Thermotex Industries Inc.; CP  
 Todd Spencer; PSAV Presentation Services; U  
 Stephen G. Surratt; Texas Scenic Company; DR  
 Peter V. Svitavsky; Wenger Corp.; CP  
 Ken Tilson; Columbus McKinnon Corp.; MP  
 Will Todd; Milos Group; MP  
 Elmer Veith; Total Structures, Inc.; MP  
 Steve Walker; Steve A. Walker & Associates; G  
 Charlie Weiner; Milos Group; MP  
 Michael Wells; Xtreme Structures and Fabrication; MP  
 Marty Wesstrom; Mountain Productions Inc.; DR  
 Jeff Wilkowski; Thern, Inc.; MP  
 Max A. Wilson; Applied Electronics; MP  
 R. Duane Wilson; Amer. Society of Theatre Consultants; DE  
 Robert Young; Arup; DE

**Observer (non-voting) members:**

Frank Allison; Frank Allison; G  
 Brent Armstrong; Alpine Rigging & Structural Design; U  
 John Van Arsdale; University of Wisconsin - Madison; U  
 William Ian Auld; Auld Entertainment; U  
 Warren A. Bacon; Warren A. Bacon; U  
 Rinus Bakker; Rhino Rigs B.V.; G  
 Robert Barbagallo; Solotech Inc.; DR  
 Roger Barrett; Star Events Group Ltd.; DR  
 F. Robert Bauer; F.R. Bauer & Associates, LLC; G  
 Maria Bement; MGM Grand; U  
 Roy Bickel; Roy Bickel; G  
 Lee J. Bloch; Bloch Design Group, Inc.; G  
 Ron Bonner; PLASA EU; G  
 William Bradburn; Aerial Arts, Inc.; U  
 Louis Bradfield; Louis Bradfield; U  
 Buddy Braile; Bestek Lighting & Staging; U  
 Barry Brazell; Barry Brazell; U  
 André Broucke; André Broucke; G  
 David M. Campbell; Geiger Engineers; G  
 Timothy Carlson; Circus Juventas; G  
 Michael J. Carnaby; Mikan Theatricals; DR  
 Daniel J. Clark; Clark-Reder Engineering, Inc.; G

Benjamin Cohen; Reed Rigging, Inc.; DR  
Ian Coles; Total Structures, Inc.; MP  
Gregory C. Collis; I.A.T.S.E. Local 16; G  
Randall W. A. Davidson; Risk International & Associates, Inc.; U  
François Deffarges; Nexo; MP  
Jim Digby; Linkin Park Touring/The Collective; U  
Noga Eilon-Bahar; Eilon Engineering Industrial Weighing Systems; MP  
James B. Evans; Mountain Productions Inc.; DR  
Tim Franklin; Theta-Consulting; G  
Luca Galante; Alfa System Sas; CP  
Tony J. Galuppi; Tony J. Galuppi; U  
Chris Geisler; Fluid Design Inc.; DE  
Sanford P. Gilzow; Shur-Rig LLC; G  
Rand Goddard; W.E. Palmer Co.; CP  
Reuben Goldberg; Technic Services; U  
Michael P. Gosenski; Rigging Systems LLC; U  
Thomas M. Granucci; San Diego State University; U  
Sean Harding; High Output, Inc.; G  
Greg Hareld; Kleege Industries; U  
Dean Hart; Freeman Companies; U  
Philip Heron; San Francisco Opera Assn.; U  
Ted Hickey; OAP Audio Products; MP  
Chris Higgs; Total Solutions Group; G  
Daniel Lynn Houser; Real Rigging Solutions, LLC; U  
Donald Hoffend\_III; Avista Designs, LLC; G  
Karl V. Sutter\_III; Kimley-Horn and Associates, Inc.; DE  
Wes Jenkins; Down Stage Right Industries; CP  
Peter Johns; Total Structures, Inc.; MP  
Kent H. Jorgensen; IATSE Local 80; G  
Gary Justesen; Oasis Stage Werks; DR  
John Kaes; John Kaes; U  
JoAnna Kamorin-Lloyd; Vincent Lighting Systems; U  
Nevin Kleege; Kleege Industries; U  
Ken P. Lager; LaFace & McGovern Associates; DR  
Jon Lagerquist; South Coast Repertory; U  
John Van Lennep; Theatrix Inc.; DR  
Mylan Lester; Creation Logics Ltd.; U  
Baer Long; Act 1 Rigging Inc.; G  
Dennis J. Lopez; Automatic Devices Co.; MP  
Jeff Lucas; Cirque Du Soleil, Inc.; G  
Darren Lucier; North Guard Fall protection Inc.; U  
Sam Lunetta; Michael Andrews; DR  
Wendy Manson; Cirque Du Soleil, Inc.; U  
Magali Marcheschi; Polytechnic Montreal; G  
Gary Mardling; Kish Rigging; DR  
Chuck McClelland; Jeamar Winches Inc.; MP  
Richard C. Mecke; Texas Scenic Company; DR

Hank Miller; W.E. Palmer Co.; CP  
John Miller; University of North Carolina School of the Arts; U  
Shaun Millington; SEW-Eurodrive, Inc.; MP  
Timothy Mills; Geiger Engineers; G  
Scott Mohr; R&R Cases and Cabinets; G  
Bartholomew J. Mueller; Recreation Engineering Inc.; DE  
John "Andrew" Munro; animaenagerie; U  
Bob Murphy; Occams Razor Technical Services; G  
Rikki Newman; Rikki Newman; U  
James Niesel; Arup; DE  
Michael Patterson; Pook Diemont & Ohl, Inc.; CP  
Ben Peoples; Pittsburgh Hoist & Sandbag Company; CP  
G. Anthony Phillips; I.A.T.S.E. Local 16; U  
Philip J. Piszczak; The National Telephone Supply Company; G  
Kurt Pragman; Pragman Associates, LLC; G  
Michael Reed; Reed Rigging, Inc.; DR  
Mark Riddlesperger; LA ProPoint, Inc.; CP  
Timo Risku; Akumek; DE  
Peter "Punch" Christian Schmidtke ; Hollywood Lighting, Inc.; DR  
Ford Sellers; Chauvet Lighting; MP  
Steven Serafin; Chubb Group of Insurance Companies; G  
Q. Brian Sickels; Q. Brian Sickels; G  
Monica Skjonberg; Skjonberg Controls, Inc.; CP  
Knut Skjonberg; Skjonberg Controls, Inc.; CP  
William Scott Sloan; William Scott Sloan; U  
Michael L. Savage, Sr.; Middle Dept. Inspection Agency, Inc.; G  
Rob Stevenson; SEW-Eurodrive, Inc.; MP  
Joachim Stoecker; CAMCO GmbH; MP  
Andy Sutton; AFX UK Ltd.; U  
Ross Taylor; Taylor & Taylor Associates; G  
Stephen Vanciel; Stephen Vanciel; U  
Michael Viehmeyer; Michael Viehmeyer; U  
Jiantong Wu; Beijing Special Engineering Design & Research Institute; G

**Interest category codes:**

CP = Custom-market Producer  
DE = Designer  
DR = Dealer or Rental company  
G = General interest  
MP = Mass-market Producer  
U = User

## Table of Contents

NOTICE and DISCLAIMER	ii
Contact Information	v
Acknowledgments	vi
1. GENERAL	1
1.1 Scope.	1
1.2 Purpose.	1
1.3 Application.	1
1.4 References.	1
2. DEFINITIONS	3
2.1 Anchorage, Certified :	3
2.2 Anchorage, PFAS:	3
2.3 Anchorage, Intermediate:	3
2.3 Anchorage Connector:	3
2.4 Deceleration Distance:	3
2.5 Free Fall Distance (FFD):	3
2.6 Horizontal:	4
2.7 Lanyard:	4
2.8 Lifeline, Horizontal (HLL):	4
2.9 Lifeline, Vertical (VLL):	4
2.10 Live Load:	4
2.11 Maximum Arrest Force (MAF):	4
2.12 Person, Authorized:	4
2.13 Person, Competent:	4
2.14 Person, Designated:	5
2.15 Person, Qualified:	5
2.16 Personal Fall Arrest System (PFAS):	5
2.17 Rescuer:	5
2.18 Rollout:	5
2.19 Self-Retracting Lanyard (SRL):	5
2.20 Structure, Portable:	5
2.21 Structure, Supported:	5
2.22 Structure, Suspended:	6
2.23 User:	6
2.24 Worker:	6
3. PORTABLE STRUCTURE REQUIREMENTS	7
3.1 General Requirements.	7
3.2 Suspended Structure Requirements.	8
3.3 Supported Structure Requirements.	9
3.4 Supported Scaffold Structure Requirements.	9
4. PFAS REQUIREMENTS	10
4.1 General.	10
4.2 Anchorage Requirements.	10
4.3 Horizontal Lifeline (HLL) Requirements.	11
4.4 Lanyard Requirements.	11

---

4.5	Rescue Requirements.	11
5.	DOCUMENTATION	12
5.1	General.	12
5.2	Hazard Analysis.	12
5.3	Rescue Plan.	12
5.4	HLL Limitation.	12
5.5	User Instructions.	12
5.6	Certified Anchorage Points.	12
6.	PFAS EQUIPMENT SELECTION, INSTALLATION, AND USE	13
6.1	General.	13
6.2	Anchorage.	14
6.3	Connector.	15
6.4	Harness.	16
6.5	Horizontal Lifeline.	16
6.6	Lanyard.	17
6.7	Self-Retracting Lanyard.	17
6.8	User Owned Equipment.	17
6.9	Vertical Lifeline.	18
7.	TRAINING	19
7.1	PFAS Users.	19
7.2	Rescuers.	19
8.	INSPECTIONS	20
9.	STORAGE	22
10.	FIGURES	23

---

## STANDARD REQUIREMENTS

EXPLANATORY INFORMATION  
(Not requirements of E1.39)

## 1. GENERAL

### 1.1 Scope.

This standard establishes minimum requirements for the selection and use of personal fall arrest systems (PFAS) on portable structures in the entertainment industry. In addition, the standard establishes minimum requirements for products and portable structures used in the service of PFAS. The requirements for other methods used to protect workers from fall hazards such as safety nets, guard rails, and rope access techniques are not included in this standard. This standard does not preclude the use of other appropriate standards to promote fall protection safety.

***E1.1** Portable structures include some scaffolding, tensile structures, tents, and suspended and supported modular truss structures*

### 1.2 Purpose.

The purpose of this document is to provide employers and workers methods for protecting workers that meet or exceed current standards for PFAS.

***E1.2** It is the intent of this document to clarify existing standards as an aid to manufacturers, employers and workers in creating a safe work environment in the entertainment industry.*

### 1.3 Application.

This standard applies to the entertainment industry. It provides PFAS requirements for workers on portable structures in theatre, musical touring, film, trade show and television, or other related industries that use similar portable structures.

### 1.4 References.

The below listed documents are listed for informational purposes. Only specifically noted sections of these documents will be incorporated into this standard by means of a reference.

ANSI E1.2 - 2013 – Entertainment Technology – Design, Manufacture and Use of Aluminum Trusses and Towers

ANSI A10.32 – 2004 – *Fall Protection*

*Systems- American National Standard for  
Construction and Demolition Operations*  
ANSI Z359.0 – 2007 – *Definitions and  
Nomenclature Used for Fall Protection and  
Fall Arrest*  
ANSI Z359.1 – 2007 – *Safety Requirements  
for Personal Fall Arrest Systems,  
Subsystems, and Components*  
ANSI Z359.2 – 2007  
ANSI Z359.3 – 2007  
ANSI Z359.4 – 2007  
ANSI Z359.6 – 2009  
ANSI Z359.12 – 2009  
ANSI Z359.13 – 2009  
CFR 1910.27 – *Fixed Ladders*  
CFR 1910.28 – *Safety Requirements for  
Scaffolding*  
CFR 1910.66 – *Appendix C – Personal Fall  
Arrest Systems*  
CFR 1926.451 – *General Requirements  
(Scaffolds)*  
CFR 1926.501-503

## STANDARD REQUIREMENTS

EXPLANATORY INFORMATION  
(Not requirements of E1.39)**2. DEFINITIONS**

**2.1 Anchorage, Certified :** An anchorage for fall arrest documented by a qualified person to be capable of supporting twice the potential forces that could be encountered during a fall.

**2.2 Anchorage, PFAS:** The terminating component of a fall protection system that is intended to support any forces applied to the system.

**2.3 Anchorage, Intermediate:** Additional supports in between the end anchorages on an HLL installation used for the purpose of reducing the total arrest distance or arrest forces at the end anchorages.

**2.3 Anchorage Connector:** A component or subsystem that functions as an interface between the anchorage and fall protection system, or rescue system for the purpose of coupling the system to the anchorage.

**2.4 Deceleration Distance:** The difference in height of a user's harness attachment at the onset of the arrest and when the worker comes to a complete stop, minus any elongation of a horizontal or vertical lifeline that occurs during the arrest.

**2.5 Free Fall Distance (FFD):** The vertical distance traveled during a fall, measured from the onset of travel to the point at which the PFAS begins to arrest the fall.

**E2.1** *Anchorage used for other purposes such as rescue would require a design factor larger than 2:1.*



**2.6 Horizontal:** The term used to describe the members that connect one top chord to the other or one bottom chord to the other on aluminum truss structures with two top chords, two bottom chords or both. This member is sometimes also referred to as a horizontal spreader.

**2.7 Lanyard:** A component consisting of a flexible rope, wire rope or strap which typically has a connector at each end for connecting to the body support at one end and to a fall arrester, energy absorber, anchorage connector or anchorage at the other end.

**2.8 Lifeline, Horizontal (HLL):** A flexible line with connectors or other coupling means at both ends for securing it horizontally between two anchorages or anchorage connectors.

**2.9 Lifeline, Vertical (VLL):** A vertically suspended flexible line along which a fall arrester travels, with a connector at the upper end for securing it to an anchorage or anchorage connector.

**2.10 Live Load:** The sum of the static loads of workers and equipment added to the structure.

**2.11 Maximum Arrest Force (MAF):** The peak force allowed on a user's body during the arrest of a fall.

**2.12 Person, Authorized:** A person who is assigned by the employer to work in a position that is exposed to a fall hazard

**2.13 Person, Competent:** A person capable of identifying existing and predictable hazards in the workplace, and authorized to take prompt corrective measures to eliminate the hazards.

**E2.12** *The term can apply to users, rescuers or other persons that meet the qualifications of the term.*

**E2.13** *See E2.12*

**2.14 Person, Designated:** A competent person designated by the workers employer to perform a task. **E2.14** See E2.12

**2.15 Person, Qualified:** A person who by possession of a recognized degree or certificate of professional standing, or who by extensive knowledge, training and experience, has successfully demonstrated the ability to solve or resolve problems relating to the subject matter and work. **E2.15** See E2.12

**2.16 Personal Fall Arrest System (PFAS):** A method of fall protection comprised of a full body harness, an anchorage and a means to connect the two, designed to arrest a free fall.

**2.17 Rescuer:** A person trained in the proper use of available rescue equipment and authorized to perform or assist in the rescue of a fallen user.

**2.18 Rollout:** An unintended disengagement of a connector caused by pressure on the affected connector's gate from the object to which it is connected.

**2.19 Self-Retracting Lanyard (SRL):** A device that automatically locks at the onset of a fall to arrest the user, but that moves freely during normal user movement.

**2.20 Structure, Portable:** An assembled system of reusable structural components specifically designed to be disassembled and moved easily.

**2.21 Structure, Supported:** An assembled system of structural components that, as a whole, bear on grade and the stability of which is provided primarily by elements acting in compression.

**2.22 Structure, Suspended:** An assembled system of structural components that, as a whole, is suspended from another existing, portable or supported structural system and the stability of which is provided primarily by elements acting in tension.

**2.23 User:** A person who performs activities when protected by a personal fall arrest system.

**2.24 Worker:** A person who performs specified tasks.

**E2.23** *As required by OSHA and current fall protection standards, all users shall be authorized to use a PFAS by the employer, who is also required to train the user prior to the user working at height.*

## STANDARD REQUIREMENTS

EXPLANATORY INFORMATION  
(Not requirements of E1.39)**3. PORTABLE STRUCTURE REQUIREMENTS****3.1 General Requirements.**

**3.1.1** All manufactured components of portable structures shall be designed and fabricated under the supervision of a qualified person.

**3.1.2** Portable structures and their components shall be used in accordance with design instructions.

**3.1.3** Where personnel access is permitted, the loads caused by a fall arrest shall be accounted for in the design of the structure.

**3.1.4** Arresting forces imposed on the portable structure by the maximum possible number of simultaneous falls shall be considered in the design of the structure.

**E3.1.4** See ANSI Z359.6-2009, Section 6.3.6 for details of how to account for multiple user falls.

**3.1.5** Provisions for PFAS shall be incorporated into the design when; (a) there is reason to believe that workers will access the structure in a fashion that would expose them to a fall hazard requiring the use of PFAS and; (b) the structure will be used where the anchorage of a PFAS to an external anchorage point is infeasible.

**3.1.6** Certified PFAS anchorages shall be designed for the simultaneous attachment of one user and one rescuer minimum.

**3.1.7** Where rescue plans can be incorporated that do not require rescuer(s) to be on the structure, it is permissible to design the certified anchorages on the structure for one user only.

**3.1.8** A qualified person shall provide a drawing detailing the locations of expected equipment loads.

**3.1.9** A qualified person shall provide a drawing detailing the maximum number of workers allowed to simultaneously access the structure and any restrictions to this number at any location on the structure.

**3.1.10** A drawing shall be provided by a qualified person detailing the location of anchorages on the structure. In addition to the location information, any restrictions to the number of users connected to the anchorage shall be listed.

**3.1.11** If the anchorage requires the use of a personal energy absorber or other special equipment, that information shall be detailed on the drawing.

## **3.2 Suspended Structure Requirements.**

**3.2.1** All loads shall be analyzed through the suspended structure system components, including any hoist components, to the supporting structure.

**3.2.2** The arresting forces shall not cause a suspension member to become unloaded during the arrest.

**3.2.3** If the structure is intended for multiple users, the structure shall be designed to limit movement caused by arresting forces.

**3.2.4** The structure shall be designed to support all equipment loads plus twice the weight of the maximum number of workers anywhere on the structure.

**E3.2.2** *The purpose is to disallow unloading in suspension tension members. As an example, the arresting force shall not cause the unloading of a chain hoist or other suspension components.*

**E3.2.4** *Due to the uncertainty involved with loading conditions associated with worker's access to these structures a factor of two shall be applied to the workers weight when determining the adequacy of the structure to support its intended loads.*

### 3.3 Supported Structure Requirements.

**3.3.1** All loads shall be analyzed through the supported structure system components.

**E3.3.1** *This would include hoist components in the event hoists are used to lift the structure and remain in place under load.*

**3.3.2** Access to a supported structure via climbing the support towers shall require the use of PFAS.

**E3.3.2** *Standard support towers do not meet the requirements for fixed ladders. See CFR 1910.27*

**3.3.3** The structure shall be designed to support all equipment loads plus twice the weight of the maximum number of workers anywhere on the structure.

**E3.3.3** *Due to the uncertainty involved with loading conditions associated with workers access to these structures a factor of two shall be applied to the workers weight when determining the adequacy of the structure to support its intended loads.*

### 3.4 Supported Scaffold Structure Requirements.

**3.4.1** When planning the construction of scaffolding, provision for the use of a PFAS during construction should be made if workers will be more than 3.05 m (10 ft) above a lower surface. The decision of whether or not to use PFAS shall be made by the designated person who is assigned by the scaffold construction entity.

**E3.4.1** *The general rule is that if there is an unprotected edge more than 1.83 m (6 ft) [OSHA 1926.501(b)(1)] above a lower surface a worker must be protected, although, while working on scaffolding this height can be increased to 3.05 m (10 ft) [OSHA 1926.451(g)(1)].*

**3.4.2** Scaffolds shall be constructed in accordance with the design of a qualified person. Scaffolds shall have a minimum strength sufficient to support the scaffold self-weight plus four times the maximum intended live load.

## STANDARD REQUIREMENTS

EXPLANATORY INFORMATION  
(Not requirements of E1.39)

## 4. PFAS REQUIREMENTS

### 4.1 General.

**4.1.1** All PFAS systems, subsystems and components shall meet the requirements of existing ANSI fall protection standards at the time of manufacture. When there is a conflict between standards, the more stringent requirement shall be met.

**4.1.2** The PFAS shall protect the user at all times, including when the user is in motion and when transferring from one system to another at height.

**4.1.3** The PFAS shall protect the user from striking the floor or other objects in the potential fall path.

**4.1.4** When calculating the total arrest distance, any deflection in the structure that would cause an increase in arrest distance shall be included.

**4.1.5** The PFAS shall be designed to limit the maximum arrest force (MAF) to 4.0 kN (900 lb) or less when connected to a portable structure.

**4.1.6** A PFAS incorporating an energy absorber shall limit the MAF to 4.0 kN (900 lb) or less and limit the deceleration distance to 1.07 m (42 in).

### 4.2 Anchorage Requirements.

The minimum anchorage ultimate strength shall be 22.2 kN (5,000 lb) per person attached, unless it is certified by a qualified person with a design factor of at least 2:1.

**E4.1.1** *In addition to a PFAS, circumstances may require users to wear other forms of personal protective equipment (PPE) such as hand protection, head protection, eye protection, etc.*

**E4.1.3** *In many cases a PFAS incorporating a horizontal lifeline (HLL) will not provide adequate protection since most require more than 6.10 m (20.0 ft) of headroom to arrest a fall.*

### **4.3 Horizontal Lifeline (HLL)**

#### **Requirements.**

Where the action of a HLL during the arrest of a fall could cause another worker to fall, the number of users in the affected span shall be limited to one.

### **4.4 Lanyard Requirements.**

All lanyards shall be equipped with energy absorbers unless the PFAS limits the free fall to less than 30cm (12 in).

### **4.5 Rescue Requirements.**

**4.5.1** When provisions for PFAS are provided on a portable structure, the employer shall provide a written rescue plan.

**4.5.2** The rescue plan shall include provisions for rescue during erection or dismantling of the portable structure if these activities require the use of PFAS.

**4.5.3** The rescue plan shall provide provisions for access to and retrieval of the fallen user.

**4.5.4** The rescue plan shall include methods of rescue, designated rescue personnel, type and location of equipment available for rescue efforts, and effective means to summon rescue personnel.

**4.5.5** If the rescue plan is dependent on a designated on-site rescue team, members of the rescue team shall not be engaged in work requiring the use of PFAS, unless after a fall there will be an adequate number of rescuers available to successfully complete the rescue.

***E4.5.4*** *Prior coordination with emergency personnel would be mandatory to use 911 as the method of retrieval of a fallen user.*



## STANDARD REQUIREMENTS

EXPLANATORY INFORMATION  
(Not requirements of E1.39)**5. DOCUMENTATION****5.1 General.**

All documentation shall be provided in writing and shall be available at the work site.

**5.2 Hazard Analysis.**

Prior to selection and installation of PFAS, a Hazard Analysis shall be provided in writing by a competent person and shall identify existing and predictable hazards on the work site.

**E5.2** See ANSI Z359.1-2007, section 7.1 for examples of hazards.

**5.3 Rescue Plan.**

The rescue plan shall comply with the provisions of section 4.5

**5.4 HLL Limitation.**

Where an HLL is used as part of a PFAS, there shall be documentation on site that specifies the following; (a) the minimum anchorage strength requirements, (b) the maximum number of simultaneous users, and (c) the minimum headroom required at the maximum length allowed by the system.

**5.5 User Instructions.**

When PFAS requires a design by a qualified person, user instructions shall be provided in writing.

**5.6 Certified Anchorage Points.**

The location and capacity of certified anchorage points shall be available to all users.

## STANDARD REQUIREMENTS

EXPLANATORY INFORMATION  
(Not requirements of E1.39)**6. PFAS EQUIPMENT SELECTION, INSTALLATION, AND USE****6.1 General.**

**6.1.1** All components of a PFAS from the anchorage connector through the full body harness shall meet the requirements of existing ANSI fall protection standards at the time of manufacture.

**6.1.2** Where PFAS anchorages are used on portable structures being suspended by hoists, each hoist shall have a rated capacity of at least 8.90kN (2,000lb) or when the hoists are used in a fashion that doubles the capacity, the hoist shall have a rated capacity of at least 4.45kN (1,000lb).

**6.1.2.1** In addition to the minimum capacity requirement, no suspension hoist shall be loaded to greater than fifty percent (50%) of its rated capacity while anchorages are being used as part of a PFAS.

**6.1.3** All components of a PFAS subjected to an arresting force shall be immediately removed from service and inspected by a competent person prior to any further use. Should any component be found defective during this inspection, it shall be removed from service and replaced prior to further use of the system.

***E6.1.3*** *As a general rule all portions of a PFAS, with the exception of retractable lifelines, are to be permanently removed from service after being subjected to an arrest force.*

**6.1.4** Knots shall only be allowed in a PFAS if the knot is an integral portion of a manufactured product that otherwise meets the requirements of existing fall protection standards. In addition, the knot shall be made permanent through the use of stitching or other methods that prevent the knot from loosening or coming untied.

**6.1.5** PFAS equipment shall be installed so that it is protected from coming into contact with hazardous objects or event conditions.

**6.1.6** PFAS shall be installed and used in a manner that will stop the user from striking a lower structure during a fall.

**6.1.7** All users shall be authorized persons prior to connecting to or otherwise making use of a PFAS.

**6.1.8** All designated rescue team members shall be authorized rescuers.

**6.1.9** The designated rescue team leader shall be a competent person in rescue techniques

## **6.2 Anchorage.**

**6.2.1** Where feasible, PFAS users working on portable structures should select anchorages located on separate permanent structures, unless certified anchorages are located on the portable structure on which the user is working.

**E6.1.5** See ANSI Z359.1-2007, section 7.1 for examples of hazards. Event conditions include but are not limited to: Pyrotechnic effects, flame projection, lighting fixtures, and CO<sub>2</sub> foggers.

**E6.1.6** Care should be taken in the selection of PFAS components to minimize the hazards associated with striking objects attached to the working surface during the arrest of a fall.

**6.2.2** Where certified anchorages are unavailable on portable structures, the employer shall have a qualified person make the determination of whether it is feasible to use the structure as an anchorage. In addition, the competent person shall train the users in the appropriate use and location of the anchorages.

**E6.2.2** *The most common anchorage location for HLLs on suspended portable structures, as noted by this task group, is the horizontal (spreader). Preliminary industry testing indicates that the 51 mm, (2 in), O.D., 3.2 mm (.125 in) wall thickness, horizontal spreaders on 521 mm and 762 mm (20.5 and 30 inch), wide trussing conforming to the requirements of ANSI E1.2 may meet the 22.2 kN (5,000 lb), strength required of a non-certified anchorage. However, the arresting force imposed on the spreader also affects the structural integrity of the structure as a whole. It is imperative that a determination be made that the addition of the arresting forces to the structure will not cause a structural failure considering any existing loads on the structure prior to the arresting force being applied.*

**6.2.3** Prior to attaching to a certified anchorage, the user shall be informed of the maximum number of simultaneous attachments for which the anchorage was designed.

**6.2.4** Anchorage connections shall be stabilized to limit movement. See Figure 01.

### **6.3 Connector.**

**6.3.1** Connectors shall be selected and used in a fashion that will minimize the potential for rollout to occur. The size of the connector and the device to which it is connected shall be such that the connector gate cannot be forced open by contact with the device during an arrest.

**E6.3.1** *Compliance with this section would eliminate snaphook to snaphook connections in most cases.*

**6.3.2** At the time of manufacture, connectors shall be individually proof tested to 16.0 kN (3,600 lb) and marked according to the requirements of the current ANSI Z359 or ANSI A10.32 standard.

**6.3.3** Connectors shall have a minimum breaking strength of 22.2 kN (5,000 lb).

**6.3.4** Only connectors specifically designed to be used in a choker configuration shall be used in that fashion.

**6.3.5** Connectors shall be properly matched to the PFAS system.

#### **6.4 Harness.**

All harnesses shall comply with section 6.1 where applicable.

#### **6.5 Horizontal Lifeline.**

**6.5.1** Where HLLs are used on portable structures the lanyard length shall be such that the maximum free fall distance (FFD) permitted by the system is 1.83 m (6 ft). When a FFD of greater than 1.83 m (6 ft) would result, a shorter lanyard shall be used.

**6.5.2** Where self-retracting lanyards (SRL) are used in conjunction with HLLs, the HLL shall be positioned such that the D-ring on the user's harness remains below the HLL.

**6.5.3** An HLL anchored to a portable structure shall be designed to require a minimum 22.2 kN (5,000 lb) strength anchorage.

**6.5.4** Where an HLL is connected to a portable structure, suspension component or hoist, all anchorage points shall be braced to limit horizontal movement due to a fall arrest force acting on the end or intermediate anchorage.

**E6.5.1** *Though 1.83m (6 ft) lanyards are very common, they may not be appropriate for this use since a free fall of greater than 1.83m (6 ft) will occur when the user's harness D-ring is above the height of the horizontal lifeline.*

**E6.5.2** *Where feasible, strong consideration should be given to using a SRL in conjunction with a HLL as the FFD will be minimized when compared to using standard lanyards.*

**6.5.4.1** Where an HLL is connected between the hoist and roundslings, the angle of the bracing shall be 45 degrees or less from horizontal. (See Figure 01)

**E6.5.4.1** *Although, to stabilize the anchorage, a small angle is desirable, it also increases the force on the slings and the structure. For this reason, angles of less than 30 degrees should be avoided.*

## **6.6 Lanyard.**

**6.6.1** Prior to using an HLL/lanyard combination that could result in a FFD of greater than 1.83m (6 ft), the user shall be instructed on how to use the combination in a fashion to prevent a FFD of greater than 1.83m (6 ft). This instruction shall be both verbal and written.

**6.6.2** The snaphook on a lanyard shall not be connected to the snaphook on an SRL.

**E6.6.2** *Generally snaphook to snaphook connections are incompatible. In addition, connecting a lanyard to an SRL can introduce increased FFD for which the SRL is not designed.*

## **6.7 Self-Retracting Lanyard.**

**6.7.1** SRLs shall be mounted at a height such that it is impossible for the lifeline to reach full retraction with the user working at the highest work level.

**E6.7.1** *Where headroom allows, the device should be suspended at least 3.05 m (10 ft) above the highest working surface on which the user could be standing while being connected to the SRL.*

**6.7.2** An SRL anchored to a portable structure shall require a minimum 22.2 kN (5,000 lb) strength anchorage.

## **6.8 User Owned Equipment.**

**6.8.1** User-owned harnesses, lanyards, and connectors are permitted, if approved for use by an employer designated competent person at the work site. However, the controlling employer has the right to refuse to allow the use of user-owned equipment.

**E6.8.1** *It is important for a competent person to evaluate the user-owned equipment in relation to its compatibility with the rest of the PFAS to which it is being attached.*

**6.8.2** User-owned equipment shall comply with the inspection requirements listed in *Section 8*.

## **6.9 Vertical Lifeline.**

**6.9.1** Only the specific lines approved by the fall arrester manufacturer shall be used as vertical lifelines (VLL).

**E6.9.1** *This section does not preclude purchasing lifelines separately from fall arrest devices, however, it does require checking with the manufacturer or the literature provided with the device to insure that the line proposed for use is approved.*

**6.9.2** Prior to use, a competent person shall ensure an approved line is used in conjunction with the fall arrest device.

**6.9.3** If a lanyard is used to connect the harness to the fall arrest device, the maximum lanyard length shall be 0.91m (3 ft).

**6.9.4** A VLL anchored to a portable structure shall require a minimum 22.2 kN (5,000 lb) strength anchorage.

## **7. TRAINING**

### **7.1 PFAS Users.**

Users shall be trained in the proper use, inspection, and limitations of the particular system, subsystems, and components to which they are attaching. This training shall take place prior to using the PFAS.

### **7.2 Rescuers.**

Authorized rescuers shall be trained in the proper use of available rescue equipment and shall also be trained in the effective retrieval of a fallen user without inflicting additional injuries to the fallen user.



## STANDARD REQUIREMENTS

EXPLANATORY INFORMATION  
(Not requirements of E1.39)**8. INSPECTIONS**

**8.1** Inspection procedures shall be performed by a competent person.

**8.2** Inspection procedures shall be performed on all fall protection equipment in use, or scheduled for use, including PFAS, portable structures and hoists.

**8.3** Inspected equipment found to be damaged or unsafe shall be removed from service immediately and clearly marked as damaged until repaired or destroyed.

**8.4** All repairs made to damaged PFAS equipment shall be performed by the manufacturer or a qualified manufacturer's representative.

**8.5** PFAS equipment shall be inspected by the user before each use.

**8.6** PFAS equipment shall be inspected by a competent person other than the user at least once a year, unless the manufacture requires more frequent inspection intervals.

**8.6.1** During the above inspection the competent person shall make the determination that the PFAS meets or exceeds the requirements of fall protection regulations in effect at the time of inspection. Any component not meeting current regulations shall be removed and replaced with a component that does meet current regulations.

**E8.2** *While portable structures and hoists can be components of a fall protection system, their inspection and repair procedures may differ from those listed in this section. See ANSI E1.2-2013 for aluminum structures inspection guidelines.*

**E8.5** *See ANSI Z359.1-2007, Section 6.1 for further details.*

**E8.6** *See ANSI Z359.1-2007, Section 6.1 for further details.*

**8.7** Equipment shall be removed from service if any of the following conditions are discovered during inspection:

- absent or illegible labels;
- absence of components causing an impairment of function, or otherwise reducing system safety or strength;
- defects in or damage to components causing an impairment of function, or otherwise reducing system safety or strength;
- alteration of components causing an impairment of function, or otherwise reducing system safety or strength;
- fading or discoloration of webbing material;
- evidence of wear on wear-mark indicators provided by the manufacturer at attachment points.

**E8.7** *For further clarification see ANSI Z359.1-2007*

## STANDARD REQUIREMENTS

EXPLANATORY INFORMATION  
(Not requirements of E1.39)**9. STORAGE**

PFAS equipment shall be properly stored after each use in accordance with manufacturer's written instruction. Proper storage may include but is not limited to the following conditions:

- in the carrying bag provided with the harness or other durable carrying bag;
- away from sharp objects, tools or hardware that may cut or fray the materials;
- out of direct sunlight;
- away from solvents, acids, or corrosive substances;
- in a dry, dark place that is free of contaminants;
- away from extreme heat or extreme cold.

Prior to storage, any moist PFAS equipment shall be air dried.

# 10. FIGURES




Figure 01